

19425 SW 89TH AVE TUALATIN, OR 97062 PHONE: (503)692-5995 FAX: (503)885-0417

EMAIL: SALES@ADVANCEDDYNAMO.COM INFO@ADVANCEDDYNAMO.COM SERVICE@ADVANCEDDYNAMO.COM

## **ADVI 500 SERIES GASOLINE GENERATORS OIL CHANGE REQUIREMENTS**

- 1. Monitor the hour meter on the control panel: Change the oil and filter based on the schedule below:
  - Change oil after an initial break-in period of a maximum of 50 hours Please note: the break-in oil is NON synthetic.
  - Thereafter, change the oil every 400 hours with full synthetic oil, 10w-30 Mobil 1 Extended Duty, or equivalent (400 Hours = 24,000 miles).
  - Note: you will need a ½" box wrench for the drain plug.

## 2. SCHEDULE OF MAINTENANCE

- Change the oil every 400 hours with full synthetic oil (10w-30 Mobil 1 Extended Duty or equivalent)
- Record the information from the hour meter on your oil change log with each oil change.
- Clean the air filter every 1,000 hours.
- Replace the air filter every 2,000 hours.

## 3. REPLACEMENT PARTS

- Use full synthetic oil 10w-30 Mobil 1 Extended Duty motor oil or equivalent (you will need 5 quarts with a filter change) for normal weather conditions (0° F / -17.8° C to 100° F / 37.8° C)
- Use full synthetic oil 5w-30 for cold weather (-20° F / -29° C to 60° F / 15.6° C) and change oil every 300 Hours.
- Use full synthetic oil 20w-50 for hot weather  $(20^{\circ} \text{ F} / -6.7^{\circ} \text{ C} \text{ to} > 100^{\circ} \text{ F} / 15.6^{\circ} \text{ C})$  and change oil every 300 hours.
- NAPA Gold #1515 oil filter (or equivalent). Note: when changing the filter, fill completely with new oil before installing.
- Donaldson # P822686 or NAPA Gold #6449 Air Filter.

**IMPORTANT:** If you are **NOT** using Mobil 1 Extended Duty motor oil, but are using a standard synthetic oil, then you must change the oil and filter every 300 hours (equivalent to 18,000 miles). If you are **NOT** using any synthetic oil, then change oil and filter every **100 hours** (equivalent to 6,000 miles).

NOTE: NOT USING THE CORRECT OIL, OIL WEIGHT, AND/OR FILTER, FOLLOWING THE PROPER OIL CHANGE SCHEDULE, AND NOT RECORDING OIL CHANGES WILL VOID THE WARRANTY.

Patent No: US 7,193,333 B1 (Patent Pending)